NETFlex+ XL Near-Edge Wax/Resin

Longer Length Efficiencies for Flexible Packaging



Benefits

- Designed for thermal transfer overprint (TTO) flexible packaging applications
- Longer length provides less ribbon changeovers
- More throughput of printed product
- 20% more ribbon with longer lengths -1100m &1200m
- Excellent print quality at all speeds up to 40 ips
- Highly compatible at various darkness/energy settings
- Produces dark, black imprints
- Anti-static formula and unique backcoat protects the printhead

Recommended Stocks

Flexible Packaging Films

- PP / Polypropylene
- PE / Polyetheylene
- PET / Polyester

Applications

- Flexible packaging
- Coffee
- Confectionary & bakery food
- Dairy
- Frozen meats/meals
- Frozen vegetables
- Medical Devices
- Nuts

Key Product Range

•	Pet	Food	and	Treats

- Pharmaceutical
- Pill packs
- Prepared foods
- Produce
- Snacks
- Spice packets
- Tray lids

STANDARD WAX	ENHANCED WAX	WAX RESIN	RESIN	NEAR EDGE
SW200	GP725	PM308	SP330	NETMark IQ
	High Mark	Prime Mark	SP575	NETFlex+
	DC100	DC200	DC400	NET330



Technical Specifications

Color Code Tab	Red		
Film Thickness	. 4 Microns		
Total Ribbon Thickness	. 5.7 Microns		
Transmission Density	. 1.5 MacBeth Scale		
Ink Melting Point 57°C / 134°F			

Imaging Characteristics

Printhead	Near-Edge
Max Print Speed	. 40 IPS (1016 mm/s)
Image Darkness	. 2.0 RD (densitometer)
Heat Resistance	. Moderate


Compliance

- REACH SVHC Free
- RoHS/WEEE
- California Proposition 65
- FDA 21CFR175
- ISEGA Approved
- Additional Regulatory Requirements Upon Request

Storage Conditions

12 months recommended 20-85% Relative Humidity Rate, 23-104°F (-5-40°C)

Performance Ratings



310 Commerce Drive • Amherst, NY 14228 Toll-Free: 888.464.4625 • Phone: 716.691.6333 salesinfo@iimak.com • www.iimak.com